

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings of claims in the application:

1. (Currently Amended) An air exchange assembly comprising:

a lower supply duct having a first lower supply duct end and a second lower supply duct end, said first lower supply duct end connected to an external cooling unit;

a bottom cap attached to said second lower supply duct end at a first end and attached to one end of a body at a second end;

an upper supply elbow mounted on a rotatable plate at another end of the body and ~~mechanically~~ communicatively connected to said bottom cap through a rotatable assembly extending through the body to the end of the body adjacent the second end of the bottom cap creating a first passage for air flow for a device to be cooled from said second lower supply duct end to said upper supply elbow through said bottom cap, wherein the rotatable plate is attached to the rotatable assembly ~~to another end of the body~~;

an upper supply duct having a first upper supply duct end and a second upper supply duct end, said first upper supply duct end connected to ~~and extending in a first direction from~~ said upper supply elbow and said second upper supply duct end connected to the a device to be cooled;

an upper return duct having a first upper return duct end and a second upper return duct end, said first upper return duct end connected to the device ~~and said second upper return duct~~

~~end connected to said upper return plenum and extending in a second direction that is substantially opposite to said first direction;~~

an upper return plenum connected to said rotatable plate and connected to said second upper return duct end;

a second passage connected to said upper return plenum;

a lower return plenum connected to said second passage creating a passage from said upper return plenum to said lower return plenum; and

a lower return duct having a first lower return duct end and a second lower return duct end, said first lower return duct end connected to said lower return plenum and said second lower return duct end connected to the external cooling unit.

2. (Currently Amended) The air exchange assembly as recited in claim 1 further comprising a slip ring assembly forming the rotatable assembly and a part of said first passage.

3. (Currently Amended) The air exchange assembly as recited in claim 2 wherein ~~the said slip ring assembly is~~ comprises a rotatable inner body and an outer body.

4. (Original) The air exchange assembly as recited in claim 1 wherein said second passage is an annular passage.

5. (Original) The air exchange assembly as recited in claim 1 further comprising an additional upper return duct and upper return plenum.

6. (Original) The air exchange assembly as recited in claim 5 further comprising a third passage for said additional upper return duct and upper return plenum.

7. (Original) The air exchange assembly as recited in claim 1 wherein said first passage is an annular passage.

8. (Currently Amended) A method for directing air flow through an air exchange assembly, the method comprising:

directing air flow from an external cooling unit through a lower supply duct to a bottom cap attached to the lower supply duct;

directing the air flow up through a first chamber connected to the bottom cap to an upper supply elbow mounted on a rotatable plate, the first chamber being formed at least in part by a rotatable assembly extending between and communicatively connecting the upper supply elbow to the bottom cap, with the rotatable assembly connected at one end to the rotatable plate and extending through the first chamber to an end of the first chamber adjacent the bottom cap;

directing the air flow from the upper supply elbow ~~in a first direction~~ through an upper supply duct to a device to be cooled;

directing the air flow from the device to be cooled to an upper return duct connected to an upper return plenum that is mounted on the rotatable plate ~~and adjacent the upper supply elbow, wherein the air flow approaches the upper return plenum from a side substantially opposite the upper supply elbow;~~ and

directing the air flow from the upper return plenum through a second chamber to a lower return plenum and through a lower return duct connected to the external cooling unit.

9. (Currently Amended) The method as recited in claim 8 wherein the rotatable assembly ~~first chamber~~ comprises a slip ring assembly forming part of the first chamber between the bottom cap and the upper supply elbow.

10. (Currently Amended) The method as recited in claim 9 wherein the slip ring assembly ~~is~~ comprises a rotatable inner body and an outer body.

11. (Original) The method as recited in claim 8 wherein the second chamber is an annular passage.

12. (Previously Presented) The method as recited in claim 8 further comprising directing the air flow to an additional upper return duct and upper return plenum.

13. (Previously Presented) The method as recited in claim 12 further comprising directing the airflow through a third chamber to the additional upper return duct and upper return plenum.

14. (Original) The method as recited in claim 8 wherein the first chamber is an annular passage.

15. (Currently Amended) An air exchange assembly comprising:

a lower supply duct means for directing air flow from an external cooling unit to a bottom cap connected to said lower supply duct means at a first end and attached to one end of a body at a second end;

a first chamber means for directing the air flow from said lower supply duct means through the bottom cap to an upper supply elbow mounted on a rotatable plate, the first chamber means being formed at least in part by a rotatable assembly extending between and communicatively connecting the upper supply elbow to the bottom cap, with the rotatable assembly connected to the rotatable plate, wherein the rotatable plate is attached to another end of the body and the rotatable assembly extends through the body to the end of the body adjacent the second end of the bottom cap;

an upper supply duct means for directing the air flow from the upper supply elbow to a device to be cooled;

an upper return duct means for directing the air flow from the device to be cooled to an upper return plenum that is mounted on the rotatable plate ~~and adjacent the upper supply elbow, wherein the air flow approaches the upper return plenum from a side substantially opposite the upper supply elbow;~~

a second chamber means for directing the air flow from the upper return plenum to a lower return plenum; and

a lower return duct means for directing the air flow from the lower return plenum to a lower return duct connected to the external cooling unit.

16. (Currently Amended) The air exchange assembly as recited in claim 15 wherein said rotatable assembly ~~first chamber means~~ comprises a slip ring assembly.

17. (Currently Amended) The air exchange assembly as recited in claim 16 wherein said slip ring assembly ~~is~~ comprises a rotatable inner body and an outer body.

18. (Original) The air exchange assembly as recited in claim 15 wherein said second chamber means is an annular passage.

19. (Previously Presented) The air exchange assembly as recited in claim 15 further comprising a third chamber means for directing the air flow to an additional upper return duct and upper return plenum.

20. (Original) The air exchange assembly as recited in claim 15 wherein the first chamber means is an annular passage.